

SAFETY DATA SHEET



Date Prepared : 05/29/2009

SDS No : Ceasolder

Date Revised : 08/21/2017

Revision No : 6

Qualitek® Ceasolder Peelable Solder Mask

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Qualitek® Ceasolder Peelable Solder Mask**PRODUCT DESCRIPTION:** Peelable Solder Mask**MANUFACTURER**

Qualitek International, Inc.

315 Fairbank St.

Addison, IL 60101

Emergency Phone: (800) 535-5053**Customer Service:** (630) 628-8083**24 HR. EMERGENCY TELEPHONE NUMBERS**

1-800-535-5053 Infotrac

1-352-323-3500 Outside the U.S.

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS**Health:**

Eye Irritation, Category 2A

GHS LABELExclamation
mark**SIGNAL WORD:** WARNING**HAZARD STATEMENTS**

H319: Causes serious eye irritation.

H333: May be harmful if inhaled.

PRECAUTIONARY STATEMENT(S)**Prevention:**

P264: Wash hands thoroughly after handling.

Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P302+P352: IF ON SKIN: Wash with plenty of water/...

P304+P341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

SAFETY DATA SHEET



Date Prepared : 05/29/2009

SDS No : Ceasolder

Date Revised : 08/21/2017

Revision No : 6

Qualitek® Ceasolder Peelable Solder Mask

Storage:

P233: Keep container tightly closed.

Disposal:

P501: Dispose of contents/container in accordance to local/regional/national/international regulations.

POTENTIAL HEALTH EFFECTS

EYES: Avoid contact with eyes; may cause redness, irritation and conjunctivitis.

SKIN: May cause skin irritation.

INGESTION: Harmful if swallowed.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

REPRODUCTIVE TOXICITY

TERATOGENIC EFFECTS: Not considered a developmental toxin.

CARCINOGENICITY: None

ROUTES OF ENTRY: Inhalation, ingestion, eye or skin contact.

CANCER STATEMENT: No data available

SENSITIZATION: May cause sensitization by inhalation and skin contact.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
Natural Rubber Centrifuged Latex	< 90	
Ammonia, aqueous	< 0.3	1336-21-6

4. FIRST AID MEASURES

EYES: Remove any contact lenses. Immediately flush eyes with large quantities of water for at least 15 minutes. Get medical attention if irritation or vision problems develop.

SKIN: Immediately wash skin with soap and copious amounts of water. Remove any contaminated clothing. Get medical attention if irritation develops. Wash contaminated clothing before reuse.

INGESTION: If person is conscious, immediately give 3-4 glasses of water or milk. Do not induce vomiting. Get immediate medical attention.

INHALATION: Move person to fresh air. If breathing is stopped or is labored, give assisted respiration (e.g. mouth-to-mouth). Supplemental oxygen may be indicated. Seek medical advice if necessary.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Stinging, tearing, redness and swelling.

SKIN: Prolonged or repeated contact may cause skin irritation.

SAFETY DATA SHEET



Date Prepared : 05/29/2009

SDS No : Ceasolder

Date Revised : 08/21/2017

Revision No : 6

Qualitek® Ceasolder Peelable Solder Mask

INGESTION: Ingestion may result in diarrhea and/or nausea.

INHALATION: Inhalation may cause respiratory tract irritation.

ACUTE EFFECTS: Low hazard for usual industrial or commercial handling.

CHRONIC EFFECTS: No adverse effects anticipated from available information.

COMMENTS: If victims of chemical over-exposure are taken for medical attention, give a copy of the label or this SDS to the physician/health care professional.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Water spray, foam, dry chemical or carbon dioxide. Do not use a full force water jet.

FIRE FIGHTING PROCEDURES: Evacuate area and fight fire from a safe distance. Immediately remove flammable material from the source of fire. Cool closed containers exposed to fire and water.

FIRE FIGHTING EQUIPMENT: Firefighters should wear NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Cover with absorbent material, soak up and sweep into a drum.

LARGE SPILL: Contain spilled liquid with sand, absorbent material, or concrete dikes for recovery or disposal. Collect spilled material for disposal in accordance with all applicable Federal, State and Local regulations.

GENERAL PROCEDURES: Absorb all spilled material on sand or vermaculite and place into closed containers for disposal. Ventilate area and wash spill site after material pickup is complete.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Store in a cool, dry, well-ventilated area. Keep containers closed and protected against physical damage. Use only in well-ventilated areas. Observe all safety precautions with empty containers as they may retain product residues. Observe all warnings and precautions listed.

HANDLING: Do not get in eyes, skin, or on clothing. Avoid breathing vapors or mists. Reasonable measures should be taken and safe practices followed with any work involving industrial chemicals.

STORAGE: Avoid freezing or excessive heat.

STORAGE TEMPERATURE: Store in a cool, dry place below 49°C (120°F).

STORAGE PRESSURE: Store at local atmospheric pressure.

SHELF LIFE: 1 Year from DOM

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide general and/or local exhaust ventilation to control airborne levels below the OSHA/ACGIH exposure guidelines.

SAFETY DATA SHEET



Date Prepared : 05/29/2009

SDS No : Ceasolder

Date Revised : 08/21/2017

Revision No : 6

Qualitek® Ceasolder Peelable Solder Mask

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Face shield, safety glasses with side shield or chemical splash goggles.

SKIN: Gloves of the following materials may provide protection against permeation: Buna, Butyl, Natural Latex, Neoprene or Solvex. Other materials may not provide adequate protection.

RESPIRATORY: Atmospheric levels should be maintained below the exposure guideline. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures and/or without sufficient ventilation, use a NIOSH/MSHA approved air-purifying respirator.

PROTECTIVE CLOTHING: Protective clothing and safety shoes as necessary to minimize contact.

WORK HYGIENIC PRACTICES: Good personal hygiene practices should be used. Wash after any contact, before eating, and at the end of the work period.

OTHER USE PRECAUTIONS: Eye wash station and quick drench safety shower in immediate work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: Ammoniacal.

APPEARANCE: Gel like liquid.

COLOR: Pink

pH: 9.5 to 11

Notes: 5 % aqueous solution (by weight)

PERCENT VOLATILE: 50

FLASH POINT AND METHOD: None

FLAMMABLE LIMITS: N/A

FREEZING POINT: 0°C (32°F)

SOLUBILITY IN WATER: Dispersible

DENSITY: 1.02 g/cc

VISCOSITY #1: 10500 to 15000 Centipoise

(VOC): 27.5 g/L (non-exempt VOC)

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Will not occur.

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid exposure to heat, open flames and other sources of ignition. Avoid contact with incompatible materials.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide and carbon monoxide.

SAFETY DATA SHEET



Date Prepared : 05/29/2009

SDS No : Ceasolder

Date Revised : 08/21/2017

Revision No : 6

Qualitek® Ceasolder Peelable Solder Mask

INCOMPATIBLE MATERIALS: Strong bases, alkali metals, and strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

DERMAL LD₅₀: > 5000 mg/kg (rabbit)

ORAL LD₅₀: 2330 mg/kg (rat)

INHALATION LC₅₀: Not Available

GERM CELL MUTAGENICITY: Not Established

REPRODUCTIVE TOXICITY: Not Established

12. ECOLOGICAL INFORMATION

GENERAL COMMENTS: No information on ecological toxicity or biodegradability is available at this time.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of this material, contaminated absorbent material and other contaminated materials in an approved waste disposal facility, according to all applicable Federal, State, and Local regulations. Recovery and reuse, rather than disposal, should be the ultimate goal in handling efforts.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not regulated by DOT

AIR (ICAO/IATA)

SHIPPING NAME: Not regulated

VESSEL (IMO/IMDG)

SHIPPING NAME: Not regulated

CANADA TRANSPORT OF DANGEROUS GOODS

SHIPPING NAME: Not regulated

15. REGULATORY INFORMATION

UNITED STATES

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: All ingredients are listed or are exempt from listing (as polymers) on the Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

SAFETY DATA SHEET



Date Prepared : 05/29/2009

SDS No : Ceasolder

Date Revised : 08/21/2017

Revision No : 6

Qualitek® Ceasolder Peelable Solder Mask

29 CFR1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS

CHEMICALS: None of the chemicals in this product are considered highly hazardous by OSHA.

CALIFORNIA PROPOSITION 65: This product does not contain materials which the state of California has found to cause cancer, birth defects or other reproductive harm.

16. OTHER INFORMATION

REASON FOR ISSUE: New format

APPROVED BY: P. Han **TITLE:** Technical Director

PREPARED BY: J. Saleda-Layton **Date Revised:** 08/21/2017

INFORMATION CONTACT: (630) 628-8083

REVISION SUMMARY: This SDS replaces the 08/31/2015 SDS.

HMIS RATING

HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

MANUFACTURER DISCLAIMER: The information contained herein is based upon data considered to be accurate and is offered solely for information, customer consideration and investigation. The manufacturer extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The content of this Safety Data Sheet relates only to this product as sold and does not relate to use with any other material or in any process. All chemical products should be used only by, or under, the direction of technically qualified personnel, who are aware of the hazards involved and of the necessity for reasonable care in handling. Hazard communication regulations, United States Occupational Health and Safety (OSHA) and Canadian Workplace Hazardous Materials Information System (WHMIS) require that employees must be trained in the use of Safety Data Sheets as a source of hazards information and response.